

JB4

"JB4": BOITE DE JONCTION AVEC PROTECTION CONTRE LES SURTENSIONS, JUSQU'A 4 CAPTEURS



Boîte de jonction simple avec protection IP67 à 4 entrées équipée de carte électronique pour la jonction des signaux de 2, 3 ou 4 capteurs. Borniers à vis pour faciliter la connexion. Le circuit de protection protège contre les foudres et les surtensions. Les coûts réduits le rendent un choix idéal pour les systèmes de pesage statiques comme silos, cuves ou récipients de grandes dimensions.

La solution idéale pour
les applications industrielles
évoluées

CARACTERISTIQUES TECHNIQUES

- Boîtier en ABS. Degré de protection IP67.
- Degré de protection IP68 avec le gel anti condensation GELBOX.
- Tension maximal en entrée 5Vdc.
- Courant maximal en entrée 700mA.
- Courant d'impulsion de crête: 15kA
- Signal maximal capteur en entrée 1000mV.
- Effet de la température : 50ppm/°C.
- Dimensions (lxwxh) : 120x80x55mm.



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE