

RF ITR

"RF2G4": INTERFACCIA RADIOFREQUENZA 2.4 GHz per PESATURA M



La soluzione ideale per
applicazioni industriali

Caratteristiche tecniche:

- Frequenza di lavoro, 2.4 GHz, fino a 39 differenti canali per poter installare più sistemi indipendenti nella stessa area di lavoro.
- Distanza di lavoro, in condizioni ambientali e di installazione adeguate: fino a 45m indoor, fino a 140m outdoor.
- Installazione integrata all'interno della bilancia.
- Non necessita di protocolli di comunicazione particolari, trasmissione in modo trasparente di qualsiasi carattere ricevuto in ingresso.



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE